

Москва (495)268-04-70	Иркутск (395)279-98-46	Новокузнецк (3843)20-46-81	Смоленск (4812)29-41-54
Архангельск (8182)63-90-72	Казань (843)206-01-48	Новосибирск (383)227-86-73	Сочи (862)225-72-31
Астана (7172)727-132	Калининград (4012)72-03-81	Омск (3812)21-46-40	Ставрополь (8652)20-65-13
Астрахань (8512)99-46-04	Калуга (4842)92-23-67	Орел (4862)44-53-42	Сургут (3462)77-98-35
Барнаул (3852)73-04-60	Кемерово (3842)65-04-62	Оренбург (3532)37-68-04	Тверь (4822)63-31-35
Белгород (4722)40-23-64	Киров (8332)68-02-04	Пенза (8412)22-31-16	Томск (3822)98-41-53
Брянск (4832)59-03-52	Краснодар (861)203-40-90	Пермь (342)205-81-47	Тула (4872)74-02-29
Владивосток (423)249-28-31	Красноярск (391)204-63-61	Ростов-на-Дону (863)308-18-15	Тюмень (3452)66-21-18
Волгоград (844)278-03-48	Курск (4712)77-13-04	Рязань (4912)46-61-64	Ульяновск (8422)24-23-59
Вологда (8172)26-41-59	Липецк (4742)52-20-81	Самара (846)206-03-16	Уфа (347)229-48-12
Воронеж (473)204-51-73	Магнитогорск (3519)55-03-13	Санкт-Петербург (812)309-46-40	Хабаровск (4212)92-98-04
Екатеринбург (343)384-55-89	Мурманск (8152)59-64-93	Саратов (845)249-38-78	Челябинск (351)202-03-61
Иваново (4932)77-34-06	Набережные Челны (8552)20-53-41	Севастополь (8692)22-31-93	Череповец (8202)49-02-64
Ижевск (3412)26-03-58	Нижний Новгород (831)429-08-12	Симферополь (3652)67-13-56	Ярославль (4852)69-52-93

Киргизия (996)312-96-26-47 Казахстан (7273)495-231 Таджикистан (992)427-82-92-69

Единый адрес для всех регионов: aga@nt-rt.ru || <https://amgo.nt-rt.ru>

CLEAR FLOOR DIRECT-DRIVED TWO-POST LIFT MODEL: A255C



Adjustable three height setting
accommodate varying service ceiling
heights.

Detailed Product Information

- Lifting capacity: 5500kg.
- Dual hydraulic direct-driven cylinders, designed and made on high standard, high quality seals.
- Self-lubricating UHMW Polyethylene sliders and bronze bush.
- Aero cable used for synchronization.
- Both insert and screw rubber pads with 3" and 6" extension adapters.
- Automatic arm locks restraints and release.
- Electric control box and manual single-point safety release.
- Overhead safety shut-off device.
- Adjustable heights accommodates varying ceiling heights.
- Clearfloor design, provide unobstructed floor space.

Model	A255C
Lifting Capacity	5500kg
Lifting Time	54S
Lifting Height	1827-2115mm
Overall Height	4192/4497mm
Overall Width	3829mm
Drive-Thru Clearance	2787mm
Width Between Columns	3137mm
Minimum Pad Height	100mm
Gross Weigh	999Kg
Motor	4.0HP